



LMP 331

Screw-In Transmitter

Stainless Steel Sensor

accuracy according to IEC 60770:
standard: 0.35 % FSO
option: 0.25 % / 0.1 % FSO

Nominal pressure

from 0 ... 100 mbar up to 0 ... 40 bar

Output signals

2-wire: 4 ... 20 mA
3-wire: 0 ... 20 mA / 0 ... 10 V
others on request

Special characteristics

- ▶ pressure port G 3/4" flush
- ▶ excellent accuracy
- ▶ small thermal effect
- ▶ excellent long term stability




Optional versions

- ▶ accuracy 0.1% FSO IEC 60770
- ▶ IS-version:
Ex ia = intrinsically safe
for gases and dusts
- ▶ SIL 2 application according to
IEC 61508 / IEC 61511
- ▶ different electrical connections
- ▶ customer specific versions
e. g. special pressure ranges

The screw-in transmitter LMP 331 has been designed for continuous level measurement and is characterized by an excellent performance and a robust construction. The modular construction allows the user the highest possible flexibility in the adaption of LMP 331.

Optional features like e.g. an intrinsically safe version or a functionally safe version (SIL 2) increase the advantages when launching and realizing projects for plants and systems.

Preferred areas of use are

-  Plant and machine engineering
-  Energy industry
-  Environmental engineering
(water – sewage – recycling)



Input pressure range															
Nominal pressure gauge	[bar]	0.10	0.16	0.25	0.40	0.60	1	1.6	2.5	4	6	10	16	25	40
Level	[mH ₂ O]	1	1.6	2.5	4	6	10	16	25	40	60	100	160	250	400
Overpressure	[bar]	0.5	1	1	2	5	5	10	10	20	40	40	80	80	105
Burst pressure ≥	[bar]	1.5	1.5	1.5	3	7.5	7.5	15	15	25	50	50	120	120	210
Vacuum resistance		p _N ≥ 1 bar: unlimited vacuum resistance								p _N < 1 bar: on request					
Output signal / Supply															
Standard		2-wire: 4 ... 20 mA / V _S = 8 ... 32 V _{DC}								SIL-version: V _S = 14 ... 28 V _{DC}					
Option IS-version		2-wire: 4 ... 20 mA / V _S = 10 ... 28 V _{DC}								SIL-version: V _S = 14 ... 28 V _{DC}					
Options 3-wire		3-wire: 0 ... 20 mA / V _S = 14 ... 30 V _{DC}								0 ... 10 V / V _S = 14 ... 30 V _{DC}					
Performance															
Accuracy ¹		standard: nominal pressure < 0.4 bar: ≤ ± 0.5 % FSO nominal pressure ≥ 0.4 bar: ≤ ± 0.35 % FSO option 1: nominal pressure ≥ 0.4 bar: ≤ ± 0.25 % FSO option 2: for all nominal pressures: ≤ ± 0.1 % FSO													
Permissible load		current 2-wire: R _{max} = [(V _S – V _{S min}) / 0.02 A] Ω current 3-wire: R _{max} = 240 Ω voltage 3-wire: R _{min} = 10 kΩ													
Influence effects		supply: 0.05 % FSO / 10 V								load: 0.05 % FSO / kΩ					
Long term stability		± ± 0.1 % FSO / year at reference conditions													
Response time ²		2-wire: ≤ 10 msec								3-wire: ≤ 3 msec					
¹ accuracy according to IEC 60770 – limit point adjustment (non-linearity, hysteresis, repeatability) ² with optional accuracy 0,1 % FSO the response time is 200 msec															
Thermal effects (Offset and Span)															
Nominal pressure p _N	[bar]	≤ 0.40								> 0.40					
Tolerance band	[% FSO]	≤ ± 1								≤ ± 0.75					
in compensated range	[°C]	0 ... 70								-20 ... 85					
Permissible temperatures															
Permissible temperatures		medium: -40 ... 125 °C				electronics / environment: -40 ... 85 °C				storage: -40 ... 100 °C					
Electrical protection															
Short-circuit protection		permanent													
Reverse polarity protection		no damage, but also no function													
Electromagnetic compatibility		emission and immunity according to EN 61326													
Mechanical stability															
Vibration		10 g RMS (25 ... 2000 Hz)								according to DIN EN 60068-2-6					
Shock		500 g / 1 msec								according to DIN EN 60068-2-27					
Explosion protection (only for 4 ... 20 mA / 2-wire)															
Approvals DX19-LMP 331		IBExU 10 ATEX 1068 X / IECEx IBE 12.0027X zone 0: II 1G Ex ia IIC T4 Ga zone 20: II 1D Ex ia IIIC T135 °C Da													
Safety technical maximum values		U _i = 28 V, I _i = 93 mA, P _i = 660 mW, C _i ≈ 0nF, L _i ≈ 0 μH, the supply connections have an inner capacity of max. 27 nF opposite the housing													
Permissible temperature for medium		in zone 0: -20 ... 60 °C with p _{atm} 0.8 bar up to 1.1 bar in zone 1 or higher: -40/-20 ... 70 °C													
Connecting cables (by factory)		cable capacitance: signal line/shield also signal line / signal line: 160 pF/m cable inductance: signal line /shield also signal line / signal line: 1 μH/m													
Materials															
Pressure port		stainless steel 1.4404 (316L)													
Housing		stainless steel 1.4404 (316L)													
Option compact field housing		stainless steel 1.4301 (304); cable gland M12x1.5, brass, nickel plated (clamping range 2 ... 8 mm)													
Seals		standard: FKM option: EPDM								others on request					
Diaphragm		stainless steel 1.4435 (316L)													
Media wetted parts		pressure port, seals, diaphragm													
Miscellaneous															
Optionally SIL 2 version ³		according to IEC 61508 / IEC 61511													
Current consumption		signal output current: max. 25 mA								signal output voltage: max. 7 mA					
Weight		approx. 200 g													
Installation position		any ⁴													
Operational life		100 million load cycles													
CE-conformity		EMC Directive: 2014/30/EU													
ATEX Directive		2014/34/EU													
³ only for 4...20mA / 2-wire; not in combination with the accuracy 0.1% ⁴ Pressure transmitters are calibrated in a vertical position with the pressure connection down. If this position is changed on installation there can be slight deviation in the zero point for pressure ranges p _N ≤ 1 bar															

LMP 331

Stainless Steel Screw-In Transmitter

Technical Data

Pin configuration					
Electrical connections	ISO 4400	Binder 723 (5-pin)	M12x1 / metal (4-pin)	compact field housing	cable colours (IEC 60757)
Supply +	1	3	1	IN +	WH (white)
Supply -	2	4	2	IN -	BN (brown)
Signal + (only for 3-wire)	3	1	3	OUT +	GN (green)
Shield	ground pin	5	4		GNYE (green-yellow)

Wiring diagrams

2-wire-system (current)

3-wire-system (current / voltage)

Electrical connections (dimensions in mm)					
standard ISO 4400 (IP 65)	options Binder series 723, 5-pin (IP 67) M12x1, 4-pin (IP 67)	 cable outlet with PVC cable (IP 67) ⁵	 cable outlet, cable with ventilation tube (IP 68) ⁶	 compact field housing (IP 67)	

⁵ standard: 2 m PVC cable (without ventilation tube, permissible temperature: -5 ... 70 °C)
⁶ different cable types and lengths available, permissible temperature depends on kind of cable

Mechanical connection (dimensions in mm)	
standard G3/4" flush (DIN 3852) with ISO 4400	SIL- and SIL-Ex-version G3/4" flush (DIN 3852) with ISO 4400

© 2020 BD|SENSORS GmbH – The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

Ordering code LMP 331

LMP 331

□	□	□	-	□	□	□	-	□	-	□	-	□	-	□	□	-	□	-	□	□	□
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

[illegible]

¹ standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70 °C), others on request

² code TR0 = PVC cable, cable with ventilation tube available in different types and lengths

³ not in combination with SIL